increments 50 mm

1400mm

1200 - 2000mm

CW= car width

CD= car depth

CH= car height

DW= door width

DH= door height P= Pit

SW= Shaft width

SD= Shaft depth

CO= overrun


ATTENTION

HR= Headroom clear

FFL= Finished floor level

Cabin protection reduces clear entrance openings resp. shaft sizes

All dimensions in "mm", DO NOT SCALE



Car Internal depth and door opening width car dependent of the type of

A-B

Typical List of builders work

Niche Lifts for details.

car door protection. Please consult

- 1. Provide electrical supply to machine room in the form of a 415v, 3ph, 50hz 5 wire supply protected by a 16amp Motor Rated MCB, together with a 230v spur.
- 2. Machine room acess by ladder
- 3. Shaft enclosure to fixed AFTER installation of lift, else leave front wall down at all levels $% \left\{ \left(1\right) \right\} =\left\{ \left(1\right) \right\}$
- 4. Shaft enclosure and shaft ventilation to be in accordance with local authority requirements
- 5. Stucture shall not carry buildings forces. Structure to be fixed to building fabric
- 6. Provide 1000 kg SWL lifting eye central above shaft
- 7. Temperature in MR room shall be between +5 ° to 40 ° constantly
- 8. Provide scaffold boards depth of shaft + 150, 3-off every 2 metres
- 9. Provide storage space on site and assistance to off load.
- 10. Note lift car delivered and installed in one section access space required
- 11. Provide barriers at each floor to guard against fall hazards
- 12. Provide 110v temp. lighting & power
- 13. Protect building fabric during egress of materials, disposal of packaging
- 14. Provide assistance with off loading and distribution of materials.

,15. Clad shaft shaft following installation.

Emission of the lift unit:
Noise level on working place of users < 70dB(A)
Electromechanical interference output below requirements of EN 55022 class B

structure to be fixed each 5m at least
Ceiling below the lift shaft must support all strengths from the lift and must be calculated with a minimum of 5 kN/m

BY	DATE	ISSUE	MODIFICATION	CHECKED	NIGHE 750 4000 L. COORS ONLY LIST THROUGH LOADING TYPICAL LAYOUT	NICHE LIFTS	Ltd F	RAWN BY DATE	CHECKED S	CALE
					NICHE 750-1000 kg GOODS ONLY LIFT THROUGH LOADING TYPICAL LAYOUT	MICHE LIFTS	LIG [TMP 25.5.0	7	NTS
					(Issued for information only)	Do not scale this drawing. All dimensions		DRAWING NUMBER		
						in millimetres			_ /.	
					NICHE LIFTS LTD 82 St Georges Road West, Bromley, Kent. BR1 2NP Tel: 020 8295 2852 Fax: 020 8467 1044 e-mail: sales@nichelifts.co.uk Web Site: www.nichelifts.co.uk			119	13/A	
					e-mail: sales@nichelifts.co.uk Web Site: www.nichelifts.co.uk				,	